

VEGA-1010

4K UHD HDMI Video Mixer



Features

- Input resolutions support from 640x480 to 4096x2160@60Hz (4:4:4 8bits), interlaced or progressive
- 4x HDMI inputs and 2x HDMI output
- Output resolution supports up to 4K2K@60Hz (4:4:4 8bits)
- Adjustable size & position through software
- Supports HDCP 2.2 compliant
- Firmware upgradable for support of new features and technology enhancements
- Titles, borders and colored backgrounds
- Resize, position, zoom & pan and blend output video
- Software control through RS-232 and Ethernet

Introduction

The VEGA-1010 4x2 HDMI 2.0a Quad-View Video Processor with 4K2K60 4:4:4 provides the most flexible and cost effective solution in the market to route ultra-high definition video source from any of the four UHD HDMI sources to the remote display at the same time. This solution is also well suited for use in digital signage, conference room presentation systems or other similar settings or applications.

With up to 4K2K60 4:4:4 output resolution, users can display the mixed video with improved presentation quality. In the meantime, the unit can be controlled thru the popular serial port and Ethernet port to provide the most flexible control way to fit into any applications.

Specifications

Model	VEGA-1010		
Role of usage	Multiplexer / video processor		
Background picture update	Yes		
HDCP compliance	1.4 / 2.2		
HDMI compliance	HDMI 2.0a		
Video bandwidth	HDMI (600MHz (18Gbps))		
Output Video Support	Up to 4K2K@60 (4:4:4 8bits)		
Input Video Support	Up to 4K2K@60 (4:4:4 8bits)		
Video Format Support	HDMI 2.0		
Audio support	Bypass		
Control	RS-232/ Ethernet/ IR / Cloud		
Embedded video mixer	Yes		
ESD protection	Human body model — ±15kV (air-gap discharge) & ±8kV (contact discharge)		
Input	4 x HDMI + 1 x RS-232 + 1 x RJ-45(Ethernet) + 1 x 3.5 mm (IR)		
Output	2 x HDMI + 2 x RCA		
HDMI connector	Type A (19-pin female)		
RS-232 connector	DE-9 (9-pin D-sub female)		
RJ-45 connector	WE/SS 8P8C		
Mechanical	Housing	Metal enclosure	
	Dimensions (L x W x H)	Model	390 x 163 x 30 mm (1.3" x 6.4" x 1.2")
		Package	494 x 225 x 70 mm (1.6" x 8.9" x 2.8")
		Carton	510 x 380 x 252 mm (1.7" x 1'2" x 10")
	Weight	Model	1.5 kg (3.3 lbs)
		Package	2 kg (4.5 lbs)
	Power supply	12V 5A DC	
	Power Consumption	22 Watts (max)	
	Operation temperature	0 ~ 40 °C (32 ~ 104 °F)	
	Storage temperature	-20 ~ 60°C (-4 ~ 140 °F)	
Relative humidity	10 ~ 90% RH (no condensation)		