

M133TG

Intel® Core™ i5-1135G7 Industrial Ultra Rugged Tablet



KEY FEATURES

- 13.3" 1920 x 1080 IPS wide viewing angle LED panel
- Intel® Core™ i5-1135G7 Tiger Lake processor
- Removeable kickstand usable as carrying handle
- Magnesium alloy housing with allaround elastomeric rubber
- IP65 waterproof and dustproof
- Fanless cooling system

INTRODUCTION

Winmate M133 Series Ultra Rugged Tablet is built for performance and durability in the toughest environments. Featuring a 13.3" sunlight-readable IPS display with optical bonding, it offers exceptional clarity and usability. Its magnesium alloy housing with elastomeric rubber ensures rugged protection, while IP65-rated waterproof and dustproof design enhances reliability. Equipped with a built-in adjustable kickstand, fanless cooling, and TPM 2.0 for security, the M133 Series is ideal for industrial applications and field operations demanding durability and efficiency.

SPECIFICATIONS

Display

Resolution	1920x1080	Size	13.3 inches
Contrast Ratio	1000:1	Panel Brightness	500.0 nits
View Angles	89,89,89,89	Type	Projected Capacitive Multi Touch
Bonding	Optical Bonding for Sunlight Viewability		

System Specification

Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)	Memory	8GB DDR4 SDRAM 16GB DDR4 SDRAM (Optional) 32GB DDR4 SDRAM (Optional)
Storage	256GB M.2 NVMe SSD Additional storage available with micro SDXC card slot 512GB M.2 NVMe SSD (Optional) 1TB M.2 NVMe SSD (Optional) 2TB M.2 NVMe SSD (Optional)	Security	Trusted Platform Module (TPM) 2.0 Kensington Lock
Operating System	Windows 10 IoT Enterprise LTSC (64 bit) Windows 11 IoT Enterprise LTSC (64 bit) (Optional)	WLAN	Support
BT	Support	WWAN	4G LTE (Optional)
GNSS	GPS/GLONASS	RFID	HF RFID reader 13.56 MHz (Optional)

Mechanical

Dimension	338.2 x 239.8 x 33.8 mm	Weight	2.4 Kg (Without Kickstand), 2.5 Kg (With Kickstand)
Cooling System	Fanless Design		

IO Ports

USB Port	3 x USB 3.0 Type A, 2 x USB 2.0 Type A, 1 x USB 3.0 Type C	Serial Port	1 x RS232 (DB9)
-----------------	--	--------------------	-----------------

SD Card Slot	1 x SDXC Slot
LAN	1 x RJ4510/100/1000 Mbps LAN
Docking Connector	1 x Docking connector

Audio	2 x 1 watt speaker
Indicator	4x LED Indicator for Power, Battery, SSD, RF status

Environment

Operating Humidity	30% to 80% RH, noncondensing	Operating Temperature	10°C to 50°C (14°F to 122°F)
Storage Temperature	20°C to 60°C (4°F to 140°F)	Shock	MILSTD810G Method 516.6 Procedure I
Vibration	MILSTD810G Method 514.6 Procedure I	IP rating	IP65
Drop	MILSTD810G Method 516.6, 4 ft	EMC	MILSTD461G CE101, CE102, RE101, RE102, CS118 (Default) MILSTD461G CS101, CS114, CS115, CS116, RS101, RS103 (Optional)

Certification

Certification	CE, FCC
----------------------	---------

Security Function

Kensington Lock	Kensington Lock Support
------------------------	-------------------------

Control

Button	1 x Power, 1 x menu, 2 x volume key 3 x Programmable Function Keys
---------------	---

Camera

Rear Camera	8MP Rear Camera with autofocus and LED light
--------------------	--

Power

Battery	15.4V, typ. 5900 mAh LiPolymer Battery (4S1P) HotSwap (Optional)	Battery Operating Time	More than 10 hours (BAPCo TabletMark v3)
Power Rating	19V DC	Adapter	100240V, 5060Hz / 19V DC

Accessory

Accessory	Adapter and Power Cord Standard Battery Stand with Integrated Handle	Optional Accessory	Vehicle Charger (Optional) Battery Charger (Optional) Desk Docking (Optional) Vehicle Dock (Optional) Stylus (Optional) Shoulder Strap (Optional) Handle (Optional)
------------------	--	---------------------------	---

Barcode Scanner

DIMENSIONS UNIT:MM

